

Tronic 4000

Key Features

- Made in Europe for quality and durability
- 50°C limit removes the need for tempering valve
- ClickFix 2.0 for fast installation
- Anti-air bubble protection safeguards heating coil
- LED indicator for operation and error status



Clickfix Easy
Installation



Electronic Air
Bubble Detection
System



Simple Digital
LED Indicator



Model		TR4001 L 13 ESOB	TR4001 L 18 ESOB	TR4001 L 27 ESOB
Part number		7736507505	7736507506	7736507507
Temperature settings	°C	Preset 50°C	Preset 50°C	Preset 50°C
Rated output power (400/415V)	kW	13/14	18/19.4	27/27.5
Circuit breaker (400/415V)	A	20/20	25/32	40/40
Switch on flow rate	L/min	2.5		
IP rating		IP25		
HxWxD	mm	484 x 236 x 106		
Weight	Kg	3.3		

Tronic 7000

Key Features

- LED display with temperature control & child lock
- Bare-wire heating for fast, efficient performance
- **AquaStop®** safety system detects and stops leaks
- Optional Wi-Fi Gateway Kit for smart monitoring



Clickfix Easy
Installation



Electronic Air
Bubble Detection
System



Digital
Multifunctional
Display



AquaStop®
Water Safety
System



Child Lock



Model		TR7001 L 18 DESOAB	TR7001 L 27 DESOAB	TR7001 18 DESOAB	TR7001 27 DESOAB
Part number		7736507508	7736507509	7736507510	7736507511
Temperature settings	°C	Adjustable from 20°C to 50°C	Adjustable from 20°C to 50°C	Adjustable from 20°C to 60°C	Adjustable from 20°C to 60°C
Rated output power (400/415V)	kW	18/19.4	27/27.5	18/19.4	27/27.5
Circuit breaker (400/415V)	A	25/32	40/40	25/32	40/40
Switch on flow rate	L/min	2.5			
IP rating		IP25			
HxWxD	mm	484 x 236 x 106			
Weight	Kg	3.8			

Tronic 8500i

Key Features

- 60°C max temperature for multiple outlets
- Built-in Wi-Fi connectivity for smart control
- Multifunctional LED colour display and consumption tracking
- **AquaStop®** safety system detects and stops leaks
- Precise temperature control



Built-in Wi-Fi



Clickfix Easy Installation



Electronic Air Bubble Detection System



Multifunctional Colour Display



AquaStop® Water Safety System



Child Lock



Model		TR8501i 18 DESOAB	TR8501i 27 DESOAB
Part number		7736507512	7736507513
Temperature settings	°C	Adjustable from 20°C to 60°C	
Rated output power (400/415V)	kW	18/19.4	27/27.5
Circuit breaker (400/415V)	A	25/32	40/40
Switch on flow rate	L/min		2.5
IP rating			IP25
HxWxD	mm	484 x 236 x 106	
Weight	Kg	3.8	

Tronic Model Drawings

Applicable to Tronic 4000, 7000, and 8500i

