

3-Phase Electric Instantaneous Water Heater

Efficient, reliable, instant hot water

Why choose Bosch?

Engineered in Germany, the Bosch Tronic 3-Phase Electric Instantaneous Water Heater range delivers high-quality, energy-efficient 3-phase electric instantaneous water heaters. Designed for builders, developers, and replacements, this range ensures on-demand hot water with superior performance and reliability.

The Bosch Tronic 4000, Tronic 7000 and Tronic 8500i feature flexible wiring options, enabling electrical connections from either the top or the two lower cable entry points. This design ensures maximum adaptability across a range of installation environments.



Product shown: Tronic 8500i *Features vary by model.



Easy and time-saving installation in 3 steps

CLICKFIX 2.0

With advanced CLICKFIX 2.0 technology and three optional electrical entry and connection points, Bosch 3-phase electric instantaneous water heaters can be installed quickly in just three simple steps – whether for new projects or replacing old systems.





bosch-homecomfort.com.au PH: 1300 30 70 37 for sales and service





3-Phase Electric Instantaneous Water Heater



Protection against water damage

AquaStop® Technology

Automatically shuts off the water when a leak is detected to prevent property damage

Product overview

Bosch 3-phase electric instantaneous water heaters provide an efficient, on-demand hot water solution. Designed to minimise energy consumption, they heat water only when needed, eliminating standby heat loss. Ideal for apartments, and commercial applications.



Tronic 4000



Tronic 7000



	Unit	TR4001			TR7001				TR8501i		
Product Type		L 13 ESOB	L 18 ESOB	L 27 ESOB	L 18 DESOAB	L 27 DESOAB	18 DESOAB	27 DESOAB	18 DESOAB	27 DESOAB	
Part Number		7736507505	7736507506	7736507507	7736507508	7736507509	7736507510	7736507511	7736507512	7736507513	
Rated output	V	400/415									
Rated Power (400/415V)	kW	13/14	18/19.4	27/27.5	18/19.4	27/27.5	18/19.4	27/27.5	18/19.4	27/27.5	
Rated current (400/415V)	A	18.8/19.5	26/27	39/39.7	26/27	39/39.7	26/27	39/39.7	26/27	39/39.7	
Circuit breaker (400/415V)	А	20/20	25/32	40/40	25/32	40/40	25/32	40/40	25/32	40/40	
Temperature settings		Preset 50°C			Adjustable from 20°C to 50°C		Adjustable from 20°C to 60°C		Adjustable from 20°C to 60°C		
Maximum allowable infeed temperature	°C	50°C			5	50°C		55°C		55°C	
Power line type		3 phases + earth without neutral									
Minimum start-up flow		2.5 l/min									
Minimum start-up pressure		0.04 Mpa (0.4 bar)									
Dimensions	mm	483 x 236 x 106mm									
Electronically controlled		1	1	1	1	1	1	1	1	1	
Setting desired temperature		х	х	х	1	1	1	1	1	1	
Installation technology CLICKFIX 2.0		1	1	1	1	1	1	1	1	1	
Touchscreen operation		Х	Х	Х	1	1	1	1	1	1	
AquaStop®		Х	Х	х	1	1	1	1	1	1	
Wi-Fi Connect		x	x	x	Optional Gateway Kit as an accessory	Optional Gateway Kit as an accessory	Optional Gateway Kit as an accessory	Optional Gateway Kit as an accessory	1	1	
Flexible connections		1	1	1	1	1	1	1	1	1	
Electronic air bubble detection		1	✓	1	1	1	1	1	1	1	
AS3498 5°C offset feature		1	1	1	1	1	х	х	х	x	



